

ELITE SERIES

EXPERIENCE SUPERIOR PERFORMANCE.

Reach the full potential of your workday with the Hauler PRO Series. With a zero-maintenance ELiTE lithium powertrain activated by Samsung SDI battery technology, the Hauler PRO Series has the power to get the job done, all while providing the benefits of zero-maintenance batteries and lower operational costs.

C

ZERO Maintenance

ELITE LITHIUM BATTERY

1500LB / 1200LB TOWING CAPACITY

1200LB / 900LB

LOAD CAPACITY

12 CU FT CARGO BED

ELITE

Page 1 of 2

www.MarsCarsLLC.com - www.CushmanCalifornia.com Phone: (714) 847-7673







HAULER PRO ELITE

HAULER PRO-X ELITE

ELITE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- · Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range

OPTIONS & ACCESSORIES

- · Limited Slip Differential
- 4-Wheel Mechanical Brakes
- . Locking Glove Box
- Bed Dividers
- . Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- 15 cu-ft Aluminum Bed with L-Track System
- . Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights High/Low Beam
- LED Taillights/Brake Lights
- Ladder/Hoop Rack (Aluminum Bed Only)
- · Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- · ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Standard Rear Receiver Hitch
- Hour Meter
- Rapid On-Board Charger

ALL-NEW //////////ATTACHMENT 8

HAULER® PRO / ELITE SERIES

HAULER PRO ELITE

HAULER PRO-X ELITE

BODY & CHASSIS

| FRAME | Welded Steel with E-Coat & DuraShield™ Powder Coat Injection Molded TPO | |
|----------------|--|--|
| BODY & FINISH | | |
| STANDARD COLOR | Forest Green | |

DIMENSIONS

| OVERALL LENGTH | 119 in (302 cm) | |
|-------------------------|---|--------------------|
| OVERALL WIDTH | 49 in (125 cm) | |
| OVERALL HEIGHT W/CANOPY | 70.5 in (179.1 cm) | 77 in (196 cm) |
| WHEEL BASE | 76.8 in (195 cm) | 77.5 in (196.9 cm) |
| FRONT WHEEL TRACK | 35 in (88.9 cm) | 38.0 in (96.56 cm) |
| REAR WHEEL TRACK | 38.5 in (97.8 cm) | |
| GROUND CLEARANCE | 4.3 in (11 cm) | 5.5 in (14 cm) |
| CARGO BOX CAPACITY | 12 cu ft (0.34 m3) | |
| CARGO BOX DIMENSIONS | 39 in (L) x 44 in (W) x 12 in (D) (99 cm x 111.8 cm x 30.5 cm) | |
| CARGO BOX MATERIAL | Roto-Molded Polyethylene | |

POWER

| POWER SOURCE | 56.7V Li-Ion Battery | |
|--------------------|---|--|
| MOTOR TYPE | ACInduction | |
| HORSEPOWER (KW) | 14.9 HP (11.1 kW) | |
| ELECTRICAL SYSTEM | 48V Primary, 12V Auxiliary | |
| BATTERY (QTY/TYPE) | 4.2 ELITE - Twin Pack | |
| BATTERY CHARGER | 811 Watt World Charger | |
| KEY OR PEDAL START | Pedal | |
| DRIVE TRAIN | Motor Shaft Direct Drive | |
| TRANSAXLE | Differential with Helical Gears | |
| SPEED CONTROLLER | 350 Amp AC Controller | |
| GEAR SELECTION | Dash Mounted Forward-Neutral-Reverse / Key Switch | |
| REAR AXLE RATIO | 16.99:1 | |
| | | |

PERFORMANCE

| OUTSIDE CLEARANCE CI | RCLE 21.5 f | 21.5 ft (6.6 m) | | |
|-----------------------|----------------------|---|--|--|
| TOWING CAPACITY | 1500 lb (680 kg) max | 1200 lb (544 kg) max | | |
| SPEED | 16.5 mph ± .05 mpl | 16.5 mph ± .05 mph (26.5 kph ± 0.8 kph) | | |
| VEHICLE LOAD CAPACITY | Y 1200 lb (544 kg) | 900 lb (408 kg) | | |
| BED LOAD CAPACITY | 800 lb (363 kg) | 500 lb (227 kg) | | |
| CURB WEIGHT | 926 lb (420 kg) | 971 lb (440 kg) | | |
| SEATING CAPACITY | 2-F | 2-Person | | |
| | | | | |

STEERING & SUSPENSION

| STEERING | Self-Compensating Rack & Pinion | | |
|----------------------|---|---------------------------|--|
| | | | |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers | | |
| SERVICE BRAKE | Dual Rear Wheel Mechanical, Self-Adjusting Drum | | |
| PARKING BRAKE | Self-Compensating, Single-Point Engagement | | |
| TIRES (FRONT & REAR) | 18 x 8.5 - 8 (6 - Ply Tires) | 20 x 8-10 (6 - Ply Tires) | |



